Technical Data Sheet

2/13/2015

Model: RKA5518CKZ (TRK5518C)

Product Description

Type:	Rotary
Application:	HBP/AC - Air Conditioning
Refrigerant:	R-407C
Voltage/Frequency:	220V 3~ 60Hz 220V 3~ 50Hz
Version:	N/A

Product Specifications

General

Evaporating Temp. Range:	-15°C to 15°C (5°F to 59°F)
Motor Torque:	Low Start Torque (LST)
Compressor Cooling:	Fan

Mechanical

Weight:	13
Weight Unit of Measure:	KG
Displacement (cc):	24.4
Oil Type:	Polyvinylether
Viscosity (cSt):	68
Oil Charge (cc):	444

Electrical

Voltage Range (50 Hz):	180-253
Voltage Range (60 Hz):	187-264
Locked Rotor Amps (LRA):	31
Rated Load Amps (RLA 50 Hz):	4.7
Rated Load Amps (RLA 60 Hz):	4.7
Max. Continuous Current (MCC in Amps):	0
Motor Resistance (Ohm) - Main:	N/A
Motor Resistance (Ohm) - Start:	N/A
Motor Type:	3PH
Overload Type:	N/A
Relay Type:	N/A

Agency Approval

CE Listed, GOST RUSSIA Listed